

CONTROLLER

SFS<sup>Topo</sup>

STONEX

[www.sfs-topo.fr](http://www.sfs-topo.fr)

# T2&T3

Rugged Tablet  
Android & Windows



- ✓ 8 inch multi-touch capacitive touchscreen
- ✓ Outdoor direct sunlight readable color display
- ✓ Wi-Fi, Bluetooth®, NFC, GSM and GNSS
- ✓ Rugged performance IP67 protection

SFS<sup>Topo</sup>

[www.sfs-topo.fr](http://www.sfs-topo.fr)

Part of **UniStrong**

# STONEX T2&T3 Rugged Tablet

## The first Stonex Rugged Tablet available in Android and Windows 10

[www.sfs-topo.fr](http://www.sfs-topo.fr)

STONEX T2 & T3, the newest member of Stonex family, reliable in terms of build quality and performance. Available in Android version (T2 - Android 5.1) and Windows version (T3 - Windows 10 Home), T2 & T3 are the perfect assistant for your field works.

Protected against water, shock and dust (IP67 class), STONEX T2 & T3 tablets offer a highly durable solution, enabling its use in even the most challenging environments.

STONEX T2 & T3 offer several fast connectivity options including WiFi, Bluetooth®, NFC, USB port, micro SDXC card slot, GSM and GPS positioning system.



## TECHNICAL FEATURES

### SYSTEM

CPU	Intel® Cherry Trail Z8350 processor T2: 1.92 GHz T3: 1.44 GHz
Operating System	T2: Android 5.1 T3: Windows 10 Home
RAM	4 GB
ROM	32 GB

### DISPLAY

Screen Size	8"
Resolution	800 x 1280 VGA
Brightness	400 Nit
Touch Panel	5 Point Capacitive

### CAMERA

Front	2 MP
Rear	5 MP

### DATA COMMUNICATION

GSM	GSM (900/1800MHz) WCDMA (900/2100MHz) HSDPA 21Mbps HSUPA 5.76 21Mbps
Bluetooth®	BT4.0 + EDR Class 1
Wi-Fi	IEEE 802.11 b/g/n
NFC	Yes
GNSS	U-blox NEO-7 support: GPS/GLONASS/QZSS
G Sensor	Yes

### INTERFACE

TF Slot	Support SDHC/SDXC x1 max: 64GB
USB Interface	USB 2.0 (Host) for Windows Android OTG
HDMI	HDMI 1.4a - Type C x 1

### POWER SUPPLY

Battery	Lithium-ion polymer battery 3.7 V - 8500 mAh
Operating time	Up to 8 hours

### PHYSICAL SPECIFICATIONS

Dimensions	228 (W) x 16.5 (D) x 147 (H) mm
Weight	630 g
Protection Class	IP67
Drop Height	1.2m composite wood floors, in operation status
Operating Temperature	-20°C to +60°C (-4°F to 140°F)
Store Temperature	-30°C to +70°C (-22°F to 158°F)
Humidity	95% non-condensing

### STANDARD CONFIGURATION

Battery Charged	Yes
Power Adaptor	3 types
USB Cable	USB to micro USB
USB Adaptor	Micro USB to USB
Strap	Yes

Illustrations, descriptions and technical specifications are not binding and may change



[www.sfs-topo.fr](http://www.sfs-topo.fr)

**SFS**  
Topo

STONEX® srl

Via Cimabue 39 - 20851 Lissone (MB) Italy  
Phone +39 039 2783008 Fax +39 039 2789576  
[www.stonexpositioning.com](http://www.stonexpositioning.com) | [info@stonexpositioning.com](mailto:info@stonexpositioning.com)